Metal ceilings

custom size

MS700XX
HOOK 700
system

CBI EUROPE
HI-TECH INTERIORS

MS700XX **HOOK 700** SYSTEM

CUSTOM SIZE







1		**2**		**3**		**4**	
MS700XX	panel pannello	**C3810PP**	primary profile profilo primario	**B100/200 300**	main runner bandraster bandraster portante		hanger bracket attacco di sospensione
5		**6**		**7**			
GA100/ 200/300	**hook between primary profile and main runner bandraster** gancio tra profilo primario e bandraster portante	**GC3810PP**	joint for primary profile giunto per profilo primario	**GB100/ 200/300**	joint for bandraster giunto per bandraster	**GU 600**	1.5 mm gasket to hide edges guarnizione autoadesiva di 1.5 mm per il mascheramento degli spigoli **(optional)**



MS700XX **square edge**
bordo angolo vivo

CUSTOM SIZE

aluminium alluminio **0.6 mm > 1 mm**
steel acciaio **0.5 mm > 1 mm**

width larghezza **300 mm > 600 mm**
length lunghezza **600 mm > 2400 mm**









SEZ. A-A



SEZ. B-B



1		2		3		4	
MS700XX	panel pannello	**C3810PP**	primary profile profilo primario	**B100/200 300**	main runner bandraster bandraster portante	hanger bracket attacco di sospensione	

5		6		7		8	
GA100/ 200/300	hook between primary profile and main runner bandraster gancio tra profilo primario e bandraster portante	**GC3810PP**	joint for primary profile giunto per profilo primario	**GB100/ 200/300**	joint for bandraster giunto per bandraster	**GU 600**	1.5 mm gasket to hide edges guarnizione autoadesiva di 1.5 mm per il mascheramento degli spigoli **(optional)**

METAL TILES *PLAFONI METALLICI*
PERFORATION PANELS *FORATURE PANNELLI*
standard width larghezza standard **< 600 mm**

perforation foratura

MICRO PERFORATION *MICRO FORATURE*

AP0/1
Ø 0.7 mm = 1,70% - parallel pitch ▪ *passo parallelo* 5 mm



AP0/2
Ø 0.7 mm = 0,46% - parallel pitch ▪ *passo parallelo* 10 mm



STANDARD PERFORATIONS *FORATURE STANDARD*

AP1/0
Ø 1.5 mm = 22,1% - diagonal pitch ▪ *passo diagonale* 4 mm



AP1/2
Ø 1.5 mm = 11% - parallel pitch ▪ *passo parallelo* 4 mm



AP1
Ø 1.5 mm = 12% - diagonal pitch ▪ *passo diagonale* 4.5 mm



AP2
Ø 2.5 mm = 16% - parallel pitch ▪ *passo parallelo* 5.5 mm



AP3
Ø 2.0 mm = 25% - diagonal pitch ▪ *passo diagonale* 3.5 mm



AP4
Ø 2.0 mm = 12.5% - parallel pitch ▪ *passo parallelo* 5 mm



AP5
Ø 2.5 mm = 4% - parallel pitch ▪ *passo parallelo* 11 mm



AP6
Ø 2.0 mm = 3% - parallel pitch ▪ *passo parallelo* 10 mm



AP07

Ø 2.5 mm = 19,6% - parallel pitch ▪ *passo parallelo* 5 mm



AP8

Ø 3.5 mm = 11,9% - parallel pitch ▪ *passo parallelo* 9 mm



AP9

Ø 3.0 mm = 19,6% - diagonal pitch ▪ *passo diagonale* 6 mm



AP10

Ø 3.0 mm = 39,3% - parallel pitch ▪ *passo parallelo* 6 mm



APQ

5 x 5 mm = 25% - parallel pitch ▪ passo parallelo 5 mm



APQ1

10 x 10 mm = 25% - parallel pitch ▪ passo parallelo 10 mm



APQ2

2 x 2 mm = 4.5% - parallel pitch ▪ passo parallelo 9.5 mm



APQ3

2 x 2 mm = 1.1% - parallel pitch ▪ passo parallelo 19 mm



APQ4

3 x 3 mm = 19% - parallel pitch ▪ passo parallelo 7 mm



APQ5

3 x 3 mm = 9.5% - parallel pitch ▪ passo parallelo 14 mm



PERIMETRAL MOLDING

standard length 3000 mm For special dimension perimetral moldings are available



20 X 24
CP10 aluminum 0.5/0.6 mm
A3000 steel 0.5/0.6 mm



24 X 40
CP20 aluminum 0.5/0.6 mm
A3002 steel 0.5/0.6 mm



24 X 40 X 20
CU4020 aluminum 0.5/0.6 mm
U3000 steel 0.5/0.6 mm



20 X 60 X 20
CU6020 aluminum 0.5/0.6 mm
U3002 steel 0.5/0.6 mm



24 X 24
CP11 aluminum 0.5/0.6 mm
A3001 steel 0.5/0.6 mm



19 X 31
CP30 aluminum 0.5/0.6 mm
A3003 steel 0.5/0.6 mm



20 X 50 X 20
CU5020 aluminum 0.5/0.6 mm
U3001 steel 0.5/0.6 mm



10 X 18 X 22
CU1822 aluminum 0.5/0.6 mm
U3003 steel 0.5/0.6 mm



15 X 20 X 25
CU2025 aluminum 0.5/0.6 mm
U3004 steel 0.5/0.6 mm



20 X 33 X 30
CU3330 aluminum 0.5/0.6 mm
U3005 steel 0.5/0.6 mm



20 X 12 X 12 X 24
CW1210 aluminum 0.5/0.6 mm
W3000 steel 0.5/0.6 mm



25 X 8 X 15 X 15
CW0815 aluminum 0.5/0.6 mm
W3002 steel 0.5/0.6 mm



24 X 20 X 20 X 24
CW2020 aluminum 0.5/0.6 mm
W3003 steel 0.5/0.6 mm



24 X 15 X 15 X 24
CW1515 aluminum 0.5/0.6 mm
W3004 steel 0.5/0.6 mm



30 X 30 X 30 X 30
CW3030 aluminum 0.5/0.6 mm
W3005 steel 0.5/0.6 mm

ACOUSTIC ABSORPTION PANELS

test: Istituto Giordano n° 196088
197140 UNI EN ISO 354: 2003

PLAIN NOT PERFORATED

HZ	100	250	500	1000	2000	4000
RI[DB]	9,8	17,3	23,1	29,1	35,0	40,8
RIFERIMENTO [DB]	8	20	27	30	31	-



AP2
PERFORATION

hole ø 2.5 mm
perforated area 16%
block fire-prof non-wovens 60 gr/m²



αs 0.31 | 0.77 | 0.78 | 0.83 | 0.82 | 0.73 **α_w= 0.85**



AP3
PERFORATION

hole ø 2.0 mm
perforated area 25%
block fire-prof non-wovens 60 gr/m²



αs 0.30 | 0.76 | 0.78 | 0.85 | 0.85 | 0.79 **α_w= 0.85**



COLOURS RANGE

STEEL / ALUMINIUM

POWDER COATED

white

RAL 9006
silver

RAL 7024
dark grey

RAL 9005
black

satin-finish aluminium

ALL RAL COLOURS

WOOD

SL57
whitened oak

SL56
cherry tree

SL252
winchester

SL02
light oak

6869
farm maple

SL28
teak

SL39
dark oak

ALUMINIUM / MAT

RAL 1015
ivory

RAL 1001
beige

RAL 1021
cadmio yellow

RAL 1007
chrome yellow

RAL 2004
orange

RAL 3002
carmine red

navy blue

RAL 5017
blue

RAL 6018
pea green

RAL 6029
mint colour

RAL 8014
brown

ALUMINIUM / BRIGHT

aisi steel
310

brass yellow
330

gold
260

The range of colours shown on this page is purely indicative, and we recommended that you request the samples. For other colours, please ask about the availability in stock.

For further details, refer to the bundle of RAL colours and CBI 's exclusive colours bundle, or contact the technical department at CBI Europe.

METAL CEILINGS & COVERINGS: technical perfection, 100% made in Italy.

CBI Europe's Metal Ceilings and Coverings systems are made up of modular elements (panels, strips or grilles) and suspended by steel support structures.
Elements are **standard or custom made**, resistant, durable, easy to handle, simple and quick to install, inspected, certified, eco-friendly and designed for new generation interiors, thanks to the architectural elements of great aesthetic versatility.

AESTETICH VERSATILITY

LIMITLESS CONFIGURATION



HI-TECH PERFORMANCES

Why

VERSATILE, FUNCTIONAL, LONG LASTING AND EASY TO INSTALL: A PERFECT COMBINATION OF TECHNOLOGY AND DESIGN THAT GUARANTEES HYGIENE AND STRENGTH.

Where

LARGE PUBLIC SPACES - HALLS, SHOPPING CENTRES, AIRPORTS, BANKS, OFFICES, CORRIDORS, STERILE ENVIRONMENTS, THEATRES, CANTEENS, HOSPITALS - OUTDOORS AND INDOORS.

Benefit

- **ACHIEVING FLEXIBLE, COMFORTABLE, CONTEMPORARY AND RESPONSIBLE INTERIORS.**
- **OBTAINING POINTS FOR LEED CERTIFICATION.**
- **SOUNDPROOFED ENVIRONMENTS.**
- **SPEEDING UP CONSTRUCTION.**
- **CONTAINING COSTS OF LABOUR AND MAINTENANCE.**
- **STRUCTURES 100% INSPECTABLE.**
- **INTEGRATION WITH ADVANCED CLIMATE CONTROL, DOMOTICS AND LIGHTING.**
- **PRECISE BUDGETING.**

FIRE REACTION

Including versions incorporating sound-absorbing non-woven fabric, are non-flammable according to the Italian Ministerial Decree of the 15th march 2005, and therefore conform to Euroclass A1 fire reaction requirements (only for not perforated panels).

HYGIENE

Easy to wash and sterilise, non-toxic, humidity resistant, and are ideal for use in kitchens, canteens, hospitals and schools.
On request, they can also be suppliedin a special fungicidal and bactericidal paint finish: tests carried out under ISO 22196 ensure the reduction of the microbial population > 95% after 24 hours. They also provide valuable protection against dust in industries producing delicate electronic circuits.

HUMIDITY RESISTANCE

Maintain their dimensional stability even under extreme ambient conditions, and can therefore be installed in environments characterised by high levels of relative humidity and large variations in temperature.
For outdoor installations, please contact CBI Europe's Technical Department.

PAINTWORK

Suspended ceilings in pre-painted aluminium and hot-galvanised and pre-painted FeP02 steel are coil-coated with primer and polyester paint to a thickness of 25 microns.
Suspended ceilings in electro-galvanised and post-painted FeP02 steel are electrostatically coated with resin based, thermosetting, polyester powder paints to a thickness of 60 microns.

LIGHT REFLECTANCE

All metal suspended ceilings finished in white and unperforated > 85% have a standard gloss level of 20.

INTEGRATED ACCESSORIES

All metal suspended ceilings can be fitted with accessories such as lighting units, ventilation vents, smoke detectors, sprinklers and suspended signage

FASTNESS

The systems are designed to guarantee rapid installation, speeding up the installation phases and respecting all the requirements of planarity and orthogonality.

ACOUSTIC ABSORPTION

Ceilings and coverings combine acoustic performance, comfort and aesthetics with adequate absorption values. Upon request they can be supplied with certifications issued by independent companies.

LEED CERTIFICATION

All products are manufactured in certified and constantly monitored processes to guarantee the highest standards of quality and safety.

ANTI-SEISMIC

The systems guarantee the application of all good safety practices in the construction and development of dedicated projects.
Upon request, they can be supplied with an anti-seismic reports, which indicate suitable bracing.

CBI EUROPE Via Mons. A.O. Romero, 14 · 60027 Osimo (AN) Italy
T +39 071 71 08 688 · fax +39 071 71 08 63 · info@cbi-europe.com · www.cbi-europe.com